



DHI-NVR5832-I/L

32 Channel 2U 8HDDs WizMind Network Video Recorder



Launched by Dahua Technology, Dahua WizMind is a full portfolio of solutions composed of project-oriented products including IPC, NVR, PTZ, XVR, Thermal and software platform which adopts industry-leading deep learning algorithms. Focusing on customer's requirements, WizMind provides precise, reliable and comprehensive AI solutions for verticals.

Overview

Dahua new NVR5000-I/L network video recorder delivers excellent performance and high recording quality that is ideally suitable for IP video surveillance applications. This NVR adopts powerful processor, providing the capability of 4K resolution processing for applications where image details are highly required. Additionally, the NVR can be served as edge storage, central storage or backup storage with an intuitive shortcut operation menu for remote management and control.

With build-in deep learning module, NVR5000-I/L series products adopt video image structuring technology based on deep learning algorithms, achieving high-precision human face recognition and perimeter protection. By applying deep learning artificial intelligence, NVR5000-I/L allows users to focus on what matters most, improves event response time and helps make video actionable.

The NVR is compatible with numerous third-party devices, which make it the perfect solution for surveillance systems that work independently of video management system (VMS).

Functions

Perimeter Protection

Automatically filtering out false alarms caused by animals, rustling leaves, bright lights, etc. Enables system to act secondary recognition for the targets. Improving alarm accuracy.

Face Recognition

Dahua Face Recognition technology extracts the features of captured faces and compares them with that in face database to recognize the person identity.

- Smart H.265+/H.265/Smart H.264+/H.264/MJPEG
- Up to 4 Channel video metadata
- Up to 12 Channel perimeter protection, SMD Plus
- Up to 4 Channel video stream face recognition
- Up to 16 face pictures/sec processing
- Up to 20 face databases with 200,000 face images in total



SMD Plus

With intelligent algorithm, Dahua Smart Motion Detection technology can categorize the targets that trigger motion detection and filter the motion detection alarm triggered by non-concerned targets to realize effective and accurate alarm.

Video Metadata

With deep learning algorithm, Dahua Video Metadata technology can detect, track, capture vehicle, non-motor vehicle and people, and select the best images, and extract attributes.

ANPR by Camera

With deep learning algorithm, Dahua ANPR technology can recognize the number plate information of vehicles in the image with ANPR cameras. Support block/allowlist mode, searching target vehicles from recorded video.

People Counting by Camera

With deep learning algorithm, Dahua People Counting technology can track and process moving human body targets to realize the accurate statistics of enter No., leave No., and In Area No. Working with management platform, it outputs yearly/monthly/weekly/daily reports to meet your requirements.

Stereo Analysis by Camara

With deep learning algorithm, Dahua People Counting technology can track and process moving human body targets to realize the accurate statistics of enter No., leave No., and In Area No. Working with management platform, it outputs yearly/monthly/weekly/daily reports to meet your requirements.


Technical Specification		Resolution	24MP, 16MP, 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 1.3MP, 720P, D1 etc.	
System		Record Mode	Manual, Schedule (Continuous, MD (Motion Detection),	
Main Processor	Multi-core embedded processor	Necord Wode	Alarm, IVS) 1–120 min (default: 60 min), Pre-record: 1–30 sec, Post-	
Operating System	Embedded LINUX	Record Interval	record: 10–300 sec	
Perimeter Protection		Raid Support	Raid0,Raid1,Raid5,Raid10	
Performance	12 channel, 10 IVS rules for each channel	Video Detection and	d Alarm	
Object classification	Human/Vehicle secondary recognition for tripwire and intrusion	Trigger Events	Alarm Out, Video Push, Email, Recording, PTZ, Tour, Snapshot, Voice Prompt, Buzzer and Screen Tips	
Al Search	Search by target classification (Human, Vehicle)	Video Detection	Motion Detection, MD Zones: 396 (22 × 18), Video Loss, Tampering and Scene Change	
Face Recognition		Alarm input	16 Channel	
	Max 16 face pictures/sec processing (modeling and comparing)	Relay Output	6 Channel	
Performance	4 channel video stream face recognition/16 channel	Playback and Backu	р	
	picture stream face recognition (with FD camera) Detect strangers' faces (not in device's face database).	Sync Playback	1/4/9/16	
Stranger Mode	Similarity threshold can be set manually.	Search Mode	Time/Date, Alarm, MD and Exact Search (accurate to second)	
Al Search	Up to 8 target face images search at same time, similarity threshold can be set for each target face image.	Backup Mode	USB Device/Network	
Database Management	Up to 20 face databases with 200,000 face images in total. Name, gender, birthday, nationality, address, ID information can be added to each face picture.	Third-party Support		
Database Application	Each database can be applied to video channels independently.	Third-party Support	Panasonic, Sony, Samsung, Axis, Pelco, Arecont, Onvif, Canon and more	
Trigger Events	Buzzer, Voice Prompts, Email, Snapshot, Recording,	Network		
ingger events	Alarm Out, PTZ Activation, etc.	Interface	2 RJ-45 Ports (10/100/1000 Mbps)	
Metadata		PoE	N/A	
Face Vehicle	Gender, age, glasses, beard, mouth mask, expression. Plate No., type, color, vehicle type, logo, plate color,	Network Protocol	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPP0E, DDNS, FTP, Alarm Server, IP Search (Support Dahua IP camera, DVR, NVS, etc.), P2P	
	ornament, calling, seatbelt, region. Top, top color, bottom, bottom color, hat, bag, gender,	Max. User Access	128 users	
Human Body	age, umbrella.	Mobile App	iPhone, iPad, Android	
Non-motor Vehicle	Type, color, number of passengers, helmet.	Interoperability	ONVIF 2.4, SDK, CGI	
Al Search	Support search target video by metadata.	Storage		
Audio and Video		Ü	8 SATA III ports, up to 10 TB for a single HDD. The	
IP Camera Input	32 Channel	Internal HDD	maximum HDD capacity varies with environment temperature	
Two-way Talk	1 Channel Input, 1 Channel Output, RCA	eSATA	1 eSATA	
Display		Auxiliary Interface	Auxiliary Interface	
Interface	2 HDMI, 1 VGA	USB	4 USB Ports (2 Rear USB 3.0, 2 Front USB 2.0)	
	HDMI1/VGA: 1920 × 1080, 1280 × 1024, 1280 × 720	RS232	1 Port, for PC Communication and Keyboard	
Resolution	HDMI2: 3840 × 2160, 1920 × 1080, 1280 × 1024, 1280 × 720	RS485	1 Port, for PTZ Control	
Decoding Capability	4-ch@8MP (30fps), 16-ch@1080P (30fps)	Electrical		
Multi-screen Display	1st Screen: 1/4/8/9/16/25/36	Power Supply	Single, AC100V–240V, 50–60 Hz	
	2nd Screen: 1/4/8/9/16	Power Consumption	NVR: <16.1W (Without HDD)	
Recording Bandwidth	320 Mbps (160 Mbps when Al function enabled)	Fan	Smart fan, automatically adjust running speed	
		Environmental		
Compression	Smart H.265+/H.265/Smart H.264+/H.264/MJPEG	Operating Conditions	-10°C to +55°C (+14°F to +131°F), 86–106kpa	


Wiz Mind | DHI-NVR5832-I/L

Storage Conditions	0°C to +40°C (+32°F to +104°F), 30-85% RH			
Construction				
Dimensions	2U, 439.7 mm \times 451.0 mm \times 94.9 mm (17.31" \times 17.75" \times 3.73")			
Net Weight	6.70 kg (14.8 lb) (without HDD)			
Gross Weight	9.30 kg (20.5 lb) (without HDD)			
Certifications				
CE	EN55032, EN55024, EN50130-4, EN62368-1			
FCC	Part 15 Subpart B, ANSI C63.4-2014			


Ordering Information				
Туре	Model	Description		
32 Channel WizMind NVR	DHI-NVR5832-I/L	32 Channel 2U 8HDDs WizMind Network Video Recorder		

Dimensions (mm[inch])





Panels



- 1 Power Switch
- 3 Netwrok Ports
- 5 USB Ports
- 7 AUDIO OUT, RCA Connector
- 9 VGA Port
- 11 RS-232 Port

- 2 Power Input Port
- 4 eSATA Port
- 6 HDMI Ports
- 8 AUDIO IN, RCA Connector
- 10 Alarm In/Out